



**CONCRETE TRANSFORMER PAD**  
**15 KV CLASS - LOOP FEED - DEAD FRONT**  
**CONCRETE MIX= 1-2 1/2 \_ 3 1/4 NOMINAL 3000 LBS**

KVA	A	B	C	D	E	F	G
75	96"	60"	54"	20"	12"	12"	55"
150	96"	60"	54"	20"	12"	12"	58"
225	96"	68"	54"	20"	12"	12"	58"
300	96"	68"	58"	20"	12"	12"	58"
500	98"	72"	58"	20"	12"	12"	58"
750	98"	78"	58"	20"	12"	12"	70"
1000	108"	84"	58"	20"	12"	12"	72"
1500	108"	106"	58"	20"	12"	12"	72"
2000	112"	108"	62"	24"	12"	15"	72"
2500	115"	108"	64"	24"	12"	18"	72"

**NOTE:** CONCRETE TO BE POURED ON UNDISTURBED SOIL, OR IF EXCAVATING IS REQUIRED, BACKFILL AND COMPACT WITH # 57 DENSE GRADE LIMESTONE



A Touchstone Energy® Cooperative

411 RING RD  
 ELIZABETHTOWN  
 KY 42701  
 1-888-637-4247  
 1-270-765-6153

**\* CONTACT NOLIN RECC PRIOR TO POURING \***

DRAWN BY JG 5/5/07 MAPPING

